



MAC MASTER[®]
T O R Q U E W R E N C H E S

HEAVY DUTY INDUSTRIAL TOOLS



Quality | Precision | Reliability | Durability



• Innovation • Performance • Safety • Accuracy



Tools for Every Industry



Precision Engineered. Performance Guaranteed.

Complete Range of Torque Wrenches and Industrial Tools for Manufacturing, Maintenance & Engineering.



SPECIAL TORQUE WRENCH



RATCHET TYPE TORQUE WRENCH



OPEN JAW TORQUE WRENCH



RING TYPE TORQUE WRENCH



STANDARD TORQUE WRENCH



INTERCHANGEABLE TORQUE WRENCH

**PRICE LIST OF
TORQUE WRENCHES**

w.e.f.

01.08.2026



SPECIFICATION OF INTERCHANGEABLE CLICK TYPE TORQUE WRENCH

Model No.	T O R Q U E R A N G E						Square Drive	OAL at Min Cap. mm			Weight Appx. (Kgs)	Price (Rs.)
	lbt. ft.		Nm		Kgf. m							
	Range	LC	Range	LC	Range	LC						
ITW 10	2-10	0.5	3-14	0.5	0.3-1.4	0.1	5/8"	342	25	35	0.6	3800
ITW 25	5-25	1	5-35	2	0.5-3.5	0.2	5/8"	365	25	35	0.65	4400
ITW 50	8-50	2	12-68	2	1-7	0.2	5/8"	490	30	42	1.15	4800
ITW 100	20-100	2	25-135	5	3-14	0.5	5/8"	587	32	49	1.75	5500
ITW 160	40-160	5	50-220	5	5-23	1	5/8"	600	32	52	5.45	5700
ITW 250	50-250	5	70-340	10	7-35	1	5/8"	804	32	52	3.10	6900

SPECIFICATION OF INTERCHANGEABLE SPANNER

S. No.	Square head size (inch)	A/F size (mm)	Length (mm)	Breadth (mm)	Thickness (mm)	Weight Appx. (kgs.)	Price (Rs.)
1	5/8	7	56.0	29.0	9	0.1	1600.00
2	5/8	8	56.0	29.0	9	0.1	1600.00
3	5/8	9	56.0	31.5	9	0.1	1600.00
4	5/8	10	56.0	31.5	9	0.1	1600.00
5	5/8	11	56.0	32.6	9	0.1	1600.00
6	5/8	12	56.0	33.8	9	0.1	1600.00
7	5/8	13	56.0	35.0	9	0.1	2000.00
8	5/8	14	56.0	36.5	9	0.1	2000.00
9	5/8	15	56.0	37.8	9	0.1	2000.00
10	5/8	16	56.0	39.0	9	0.1	2000.00
11	5/8	17	56.0	40.3	9	0.1	2000.00
12	5/8	18	58.0	46.6	11	0.15	2000.00
13	5/8	19	58.0	47.8	11	0.15	2000.00
14	5/8	20	58.0	49.0	11	0.15	2400.00
15	5/8	21	58.0	50.3	11	0.20	2400.00
16	5/8	22	58.0	51.5	11	0.20	2400.00
17	5/8	24	58.0	51.5	11	0.20	2400.00
18	5/8	25	68.0	59.8	14	0.25	2400.00
19	5/8	26	68.0	61.0	14	0.25	2400.00
20	5/8	27	68.0	62.2	14	0.25	2600.00
21	5/8	28	68.0	63.5	14	0.28	2600.00
22	5/8	29	68.0	64.8	14	0.28	2600.00
23	5/8	30	68.0	66.0	14	0.35	2600.00
24	5/8	32	68.0	68.5	14	0.35	3500.00
25	5/8	33	68.0	69.8	14	0.38	3500.00
26	5/8	34	68.0	71.0	14	0.38	3500.00
27	5/8	35	68.0	72.8	14	0.40	3500.00
28	5/8	36	68.0	73.5	14	0.40	3500.00



SPECIFICATION OF STANDARD TYPE CLICK TORQUE WRENCH

Model No.	T O R Q U E R A N G E						Square Drive (inch)	OAL at Min Cap. (mm)	Head Width (mm)	Head Depth (+ Bit) (mm)	Weight Appx. (Kg.)	Price (INR)
	lbt. ft.		N.m		Kgf. m							
	Range	LC	Range	LC	Range	LC						
TW 10	2-10	0.5	3-14	0.5	0.3-1.4	0.1	3/8"	310	25	35	0.55	3800
TW 25	5-25	1	5-35	2	0.5-3.5	0.2	3/8"	340	25	35	0.6	4000
TW 50	8-50	2	10-68	2	1-7	0.2	1/2"	458	30	42	1.0	4600
TW 75	15-75	2	20-100	5	2-10	0.5	½"	570	32	49	1.70	4800
TW 100	20-100	2	25-135	5	3-14	0.5	1/2"	570	32	49	1.75	4800
TW 150	30-150	5	40-200	5	4-20	1	1/2"	590	32	52	2.30	5000
TW 160	40-160	5	50-220	5	5-23	1	1/2"	590	32	52	2.30	5000
TW 250	50-250	5	70-340	10	7-35	1	1/2"	790	32	52	2.90	5800
TW 300	60-300	5	80-400	10	8-40	1	1/2"	790	32	52	2.90	6600
TW 400	100-400	10	135-540	15	14-56	1	3/4"	1020	48	62	6.50	10800
TW 500	100-500	10	135-675	15	14-70	2	3/4"	1020	48	62	6.50	12300
TW 600	145-605	10	200-815	15	20-84	2	3/4"	1020	48	62	6.70	13700
TW 745	145-745	10	200-1010	15	20-102	2	3/4"	1020	48	62	6.70	19300
TW 750	350-750	20	475-1015	20	49-105	2	3/4"	1260	56	72	12.0	19300
TW 750S	350-750	20	475-1015	20	49-105	2	1"	1260	61	82	12.0	20500
TW 1000	400-1000	20	540-1380	40	55-140	5	1"	1320	70	83	13.5	24000
TW 1400	750-1400	25	1000-1900	50	105-195	5	1"	1380	70	83	15.0	33900
TW 2000	1000-2000	50	1350-2700	50	135-275	5	1"	1430	70	83	16.5	47800
TW 2500	1500-2500	50	2030-3430	50	207-347	5	1"	1510	70	83	20.5	50800
TW 3000	1400-3000	50	1900-4050	50	193-413	5	1"	1620	70	83	21.5	56000
MSD-15			0.1-1.5				1/4"	156			0.25	5300
MSD-50			1-5				1/4"	156			0.50	6500



SPECIFICATION OF RATCHET TYPE CLICK TORQUE WRENCH

Model No.	T O R Q U E R A N G E						Square Drive (inch)	OAL at Min Cap. (mm)	Head Width (mm)	Head Depth (+ Bit) (mm)	Weight Appx. (Kg.)	Price (INR)
	lbt. ft.		N.m		Kgf. m							
	Range	LC	Range	LC	Range	LC						
TW 10R	2-10	0.5	3-14	0.5	0.3-1.4	0.1	3/8"	350	36	35	0.75	4100
TW 25R	5-25	1	5-35	2	0.5-3.5	0.2	3/8"	380	36	35	0.75	4600
TW 50R	8-50	2	10-68	2	1-7	0.2	1/2"	495	42	42	1.20	5300
TW 75R	15-75	2	20-100	5	2-10	0.5	1/2"	600	50	49	2.00	6300
TW 100R	20-100	2	25-135	5	3-14	0.5	1/2"	600	50	49	2.00	6300
TW 150R	30-150	5	40-200	5	4-20	1	1/2"	610	50	52	2.50	6400
TW 160R	40-160	5	50-220	5	5-23	1	1/2"	610	50	52	2.50	6400
TW 250R	50-250	5	70-340	10	7-35	1	1/2"	820	50	52	3.10	7200
TW 300R	60-300	5	80-400	10	8-40	1	1/2"	820	50	52	3.10	7900
TW 400R	100-400	10	135-540	15	14-56	1	3/4"	1090	72	62	7.40	12200
TW 500R	100-500	10	135-675	15	14-70	2	3/4"	1090	72	62	7.40	14600
TW 600R	145-605	10	200-815	15	20-84	2	3/4"	1090	72	62	7.60	15700
TW 745R	145-745	10	200-1010	15	20-102	2	3/4"	1090	72	62	7.60	25000
TW 750R	350-750	20	475-1015	20	49-105	2	3/4"	1350	79	72	13.0	25000
TW 750RS	350-750	20	475-1015	20	49-105	2	1"	1350	79	72	13.0	26500
TW 1000R	400-1000	20	540-1380	40	55-140	5	1"	1420	100	83	16.5	28200
TW 1400R	750-1400	25	1000-1900	50	105-195	5	1"	1480	100	83	18.0	37300
TW 2000R	1000-2000	50	1350-2700	50	135-275	5	1"	1530	100	83	20.0	52000
TW 2500R	1500-2500	50	2030-3430	50	207-347	5	1"	1630	100	83	24.0	55600
TW 3000R	1400-3000	50	1900-4050	50	193-413	5	1"	1720	100	83	25.0	62700



SPECIFICATION OF TORQUE MULTIPLIER

S. No.	Model Name	Input size (Inchs)	Output size (Inchs)	Multiplication Factor	Capacity (N.M)	Recommended Torque Wrench	Price (Rs.)
1	MMT-6100	1/2"	1-1/2"	25	6100	250R	91000.00
2	MMT-8100	1/2"	1-1/2"	25	8100	250R	100000.00
3	MMT-10000	3/4"	1-1/2"	25	10000	400R	190000.00
4	MMT-13500	3/4"	2-1/2"	25	13500	500R	238000.00
5	MMT-2700	3/4"	1"	5	2700	500R	32000.00
6	MMT-800	1/2"	3/4"	4	800	160R	25000.00
7	MMT-1700	1/2"	3/4"	6	1700	250R	25000.00
8	MMT-3390	1/2"	1"	25	3390	100R	51000.00
9	MMT-1700	1/2"	3-4"	5	1700	250R	25000.00
10	MMT-4000	1/2"	1-1/2"	25	4000	160R	58000.00

SPECIFICATION OF REVERSIBLE RATCHET TYPE TORQUE WRENCH

Model No.	T O R Q U E R A N G E						Square Drive	OAL at Min Capacity	Head Width	Head Depth (with Bit)	Weight Appx. (Kg)	Price (INR)
	lbt. ft.		Nm		Kgf. m							
	Range	LC	Range	LC	Range	LC						
TW 10R	2-10	.5	3-14	.5	.3-1.4	.1	3/8	345	36	35	0.65	4850
TW 25R	5-25	1	5-35	2	.5-3.5	.2	3/8	375	36	35	0.70	5350
TW 50R	8-50	2	12-68	2	1-7	.2	1/2	495	42	42	1.10	5750
TW 100R	20-100	2	25-135	5	3-14	.5	1/2	590	48	49	1.90	6350
TW 160R	40-160	5	50-220	5	5-23	1	1/2	600	48	52	2.50	6550
TW 250R	50-250	5	70-340	10	7-35	1	1/2	810	48	52	3.00	7650

TORQUE WRENCH ACCESSORIES

PART NO.	DESCRIPTION	UNIT PRICE (RS.)
Special Square Bit	3/8" Sq. Dr. x 1/2"	500.00
Special Square Bit	1/2" Sq. Dr. x 3/4"	880.00
Special Square Bit	3/4" Sq. Dr. x 1"	1490.00
Special Square Bit	1/2" Sq. Dr. x 3/8"	550.00
Special Square Bit	1/2" Sq. Dr. x 3/4"	880.00
Special Square Bit	3/4" Sq. Dr. x 1/2"	960.00
Special Square Bit	3/4" Sq. Dr. x 1"	1490.00
Special Square Bit	1" Sq. Dr. x 3/4"	1500.00
Square Bit	3/8" Sq. Dr.	340
Square Bit	1/2" Sq. Dr.	440
Square Bit	3/4" Sq. Dr. x 62	560
Square Bit	3/4" Sq. Dr. x 72	740
Square Bit	1" Sq. Dr.	1120
Square Bit	1. 1/2"	2100
Ratchet Head	3/8"	2700
Ratchet Head	1/2"	2800

****Disclaimer****

The information, specifications, illustrations, and product designs contained in this catalogue are provided for general reference only. We reserve the right to modify, improve, or discontinue any product design, specification, or feature at any time without prior notice. While every effort has been made to ensure the accuracy of the information presented, the latest product details may differ from those shown in this catalogue.



MAC MASTER TOOLS PVT. LTD.

Dera Bassi Unit :

Plot No. E-66, Foacal Point, Dera Bassi (Punjab)-140507

contact@macmasterindia.com

www.macmasterindia.com

www.macmastertools.in